



Solid, simple and smart:
advanced reliability in compressed air

FONOCOMPACT PRO 1.5-7.5 kW/2-10 hp



FONOCOMPACT PRO: your work floor companion

The Ceccato FONOCOMPACT PRO combines performance with comfort like no other piston compressor. Ultra-quiet and easy to use, the FONOCOMPACT PRO gives you reliable and powerful pneumatic support right on your work floor. With a power range from 2 to 10 hp, and flexible options for air storage and treatment, a FONOCOMPACT PRO model is always available to fit your needs.



Extra quiet

Optimized canopy design minimizes sound levels.



Easy to use

Intuitive control panel with pressure gauge and hour counter.



Compact

All-in-one design reduces the unit's footprint.



The integrated quality air solution

If you need dry, high-quality air, the FONOCOMPACT PRO series is available with an integrated refrigerant dryer for a compact all-in-one solution.



A flexible go-getter

Strong performance

The FONOCOMPACT PRO packs a punch in a small frame. Its new pump was designed to give you a strong, energy-efficient performance and superior reliability. A dedicated cooling fan ensures smooth operation, even in hot and dusty conditions.



Always dependable

When you have things to do, you can't afford your compressor to break down. The FONOCOMPACT PRO's high-efficiency piston pump with low rotation speed delivers exceptional reliability and a long lifetime.

Flexible storage

To ensure stable air delivery, the FONOCOMPACT PRO offers a range of air storage options. For those with limited space, the floor-mounted unit comes with an integrated 27-liter air vessel. If you need more storage, tank-mounted models are available with 270-liter or 500-liter vessels.



The right FONOCOMPACT PRO to meet your needs

FONOCOMPACT PRO 27 F2 - 27 F3

2-3 hp / 1.5-2.2 kW

- Extra quiet for comfortable work floor operation.
- Easy to operate and maintain.
- Integrated 27-liter air vessel ensures a stable air supply.
- Built for safety with fire-proof insulating foam and metal belt guard.
- Ideal for small pneumatic jobs.



FONOCOMPACT PRO 100 F3 / FONOCOMPACT PRO 500 F5

3-5 hp / 2.2-4 kW

- New NS31 pump delivers increased performance and reliability.
- Canopy was designed specifically to minimize sound.
- Available in floor-mounted and tank-mounted (270 and 500-liter) models.
- All-in-one design reduces the unit's footprint.
- Ideal for automotive service stations.



FONOCOMPACT PRO F6 / FONOCOMPACT PRO 500 F10

5.5-10 hp / 4-7.5 kW

- Flexible air storage options with floor-mounted and tank-mounted (270 and 500-liter) models.
- Heavy-duty cooling system with dedicated fan for dependable operation in all conditions.
- Can be outfitted with integrated dryer for an all-in-one quality air solution.
- Ideal for workshops and carpentry shops.



Extra quiet



Compact



Easy to use



Integrated vessel



Improved reliability

FONOCOMPACT PRO 27 F2 - 27 F3 2-3 hp

Description	Power	Pressure	Pump	Pump RPM	Displacement	Vessel	Noise	Voltage	Dimensions	Weight	Outlet
	HP	bar	Type	Min ⁻¹	l/min	L.	Lp(4m)	V / ph / Hz	L x W x H	KG	Connection
FONOCOMPACT PRO 27 F2SM	2	10	NS12S	1075	255	27	61	230/1/50	735x430x845	86	1/4" G
FONOCOMPACT PRO 27 F2S	2	10	NS12S	1075	255	27	61	400/3/50	735x430x845	86	1/4" G
FONOCOMPACT PRO 27 F3SM	3	10	NS12S	1350	320	27	62	230/1/50	735x430x845	87	1/4" G
FONOCOMPACT PRO 27 F3S	3	10	NS12S	1350	320	27	62	400/3/50	735x430x845	87	1/4" G



High performance



Extra quiet



Flexible storage



Compact



Improved reliability

FONOCOMPACT PRO 100 F3 / FONOCOMPACT PRO 500 F5 3-5 hp

Description	Power	Pressure	Pump	Pump RPM	Displacement	Vessel	Noise	Voltage	Dimensions	Weight	Outlet
	HP	bar	Type	Min ⁻¹	l/min	L.	Lp(4m)	V / ph / Hz	L x W x H	KG	Connection
FONOCOMPACT PRO 100 F3SM	3	10	NS19S	1050	393	100	65	230/1/50	1002x1227x580	220	1/2" G
FONOCOMPACT PRO 100 F3S	3	10	NS19S	1050	393	100	65	400/3/50	1002x1227x580	220	1/2" G
FONOCOMPACT PRO 270s F3SM	3	11	NS19S	1050	393	270	65	230/1/50	1522x580x1242	248	1/2" G
FONOCOMPACT PRO 270s F3S	3	11	NS19S	1050	393	270	65	400/3/50	1522x580x1242	248	1/2" G
FONOCOMPACT PRO 270 F3SM	3	11	NS31	1050	444	270	65	230/1/50	1522x580x1242	248	1/2" G
FONOCOMPACT PRO 270 F3S	3	11	NS31	1050	444	270	65	400/3/50	1522x580x1242	248	1/2" G
FONOCOMPACT PRO F4S	4	11	NS31	1300	553	0	69	400/3/50	750x580x710	170	3/4" G
FONOCOMPACT PRO 270 F4S	4	11	NS31	1300	553	270	69	400/3/50	1522x580x1242	248	1/2" G
FONOCOMPACT PRO F5S	5	11	NS31	1400	598	0	69	400/3/50	750x580x710	170	3/4" G
FONOCOMPACT PRO 270 F5S	5	11	NS31	1400	598	270	69	400/3/50	1522x580x1242	248	1/2" G
FONOCOMPACT PRO 500 F5S	5	11	NS31	1400	598	500	69	400/3/50	1937x600x1348	274	3/4" G



High performance



Extra quiet



Flexible storage



Compact



Quality air

FONOCOMPACT PRO F6 / FONOCOMPACT PRO 500 F10 5.5-10 hp

Description	Power	Pressure	Pump	Pump RPM	Displacement	Vessel	Noise	Voltage	Dimensions	Weight	Outlet
	HP	bar	Type	Min ⁻¹	l/min	L.	Lp(4m)	V / ph / Hz	L x W x H	KG	Connection
FONOCOMPACT PRO F6S	5	11	NS39	1010	660	0	65	400/3/50	1000x741x955	153	3/4" G
FONOCOMPACT PRO F6XS	5	11	NS39	1010	660	0	65	400/3/50	1000x741x955	157	3/4" G
FONOCOMPACT PRO 270 F6S	5	11	NS39	1010	660	270	65	400/3/50	1517x741x1487	220	1/2" G
FONOCOMPACT PRO 270 F6XS	5	11	NS39	1010	660	270	65	400/3/50	1517x741x1487	224	1/2" G
FONOCOMPACT PRO 500 F6S	5	11	NS39	1010	660	500	65	400/3/50	1943x741x1593	253	3/4" G
FONOCOMPACT PRO 500 F6XS	5	11	NS39	1010	660	500	65	400/3/50	1943x741x1593	257	3/4" G
FONOCOMPACT PRO 500 F6SE	5	11	NS39	1010	660	500	65	400/3/50	1943x767x1596	265	3/4" G
FONOCOMPACT PRO 500 F6XSE	5	11	NS39	1010	660	500	65	400/3/50	1943x767x1596	269	3/4" G
FONOCOMPACT PRO F8S	7	11	NS39	1140	750	0	68	400/3/50	1000x741x955	229	3/4" G
FONOCOMPACT PRO F8XS	7	11	NS39	1140	750	0	68	400/3/50	1000x741x955	235	3/4" G
FONOCOMPACT PRO 500 F8S	7	11	NS39	1140	750	500	68	400/3/50	1943x741x1593	355	3/4" G
FONOCOMPACT PRO 500 F8XS	7	11	NS39	1140	750	500	68	400/3/50	1943x741x1593	361	3/4" G
FONOCOMPACT PRO 500 F8SE	7	11	NS39	1140	750	500	68	400/3/50	1943x767x1596	367	3/4" G
FONOCOMPACT PRO 500 F8XSE	7	11	NS39	1140	750	500	68	400/3/50	1943x767x1596	371	3/4" G
FONOCOMPACT PRO F10S	10	11	NS59	810	1020	0	66	400/3/50	1000x741x955	248	3/4" G
FONOCOMPACT PRO F10XS	10	11	NS59	810	1020	0	66	400/3/50	1000x741x955	254	3/4" G
FONOCOMPACT PRO 500 F10S	10	11	NS59	810	1020	500	66	400/3/50	1943x741x1593	399	3/4" G
FONOCOMPACT PRO 500 F10XS	10	11	NS59	810	1020	500	66	400/3/50	1943x741x1593	411	3/4" G
FONOCOMPACT PRO 500 F10SE	10	11	NS59	810	1020	500	66	400/3/50	1943x767x1596	415	3/4" G
FONOCOMPACT PRO 500 F10XSE	10	11	NS59	810	1020	500	66	400/3/50	1943x1593x738	513	3/4" G

YD = star-delta start T = integrated refrigerant dryer



Contact your local representative:

www.ceccato.com

6999100540



CARE

Care is what service is all about: professional service by knowledgeable people, using high-quality original parts.

TRUST

Trust is earned by delivering on our promises of reliable, uninterrupted performance and long equipment lifetime.

EFFICIENCY

Equipment efficiency is ensured by regular maintenance. Efficiency of the service organization is how Original Parts and Service make the difference.

© 2020, Ceccato. All rights reserved. All mentioned brands, product names, company names, trademarks and service marks are the properties of their respective owners. Our products are constantly being developed and improved. We thus reserve the right to modify product specifications without prior notice. Pictures are not contractually binding.

