



# User benefits

## Simple Installation

- Compact and all in one system, thanks to the oversized integrated dryers.
   Compressed air quality can be improved by the cyclonic water separator and the coalescent filter is available as an option.
- Innovative design
- Easy and fully protected transport
- No special foundation needed

## Solid Quality

Outstanding and first-class components:

- Highly reliable transmissions, for a quiet and trouble-free operation.
- High capacity oil/air coolers, perfect air filtration and cooling guarantee less thermal shocks and a longer lifetime.
- Overload protection and full automatic
- High quality and heavy duty motor.

# Easy Maintenance and Accessibility

- All service components are located at the front of the machine for excellent accessibility, you just have to open the frontal door for an easy access for service or cleaning, easy access of the coolers, oil filter, separator and air filter replacements.
- Oil-level eye at the front
- Easy and quick check thanks to service door and controller
- Service and cleaning is a one person job

### Saving of costs

- Lower energy consumption thanks to IE3 motors or IVR technology
- Optimal efficiency, lubrication and cooling
- Long service intervals

#### Safety

- Emergency stop
- Protection grid
- IP 54 electrical cubicle
- Internal and external protection for the electric fan.

# >>> DRB 30-50 Gear driven DRB 30-50 IVR Direct driven

Compressed air drives your company. Consequently, choosing the right compressor is crucial. Going for our DRB and DRB IVR ranges of highly efficient and flexible oil-injected screw compressors is a choice you will not regret. Bring some fresh air into your company and enjoy the strong performance and high efficiency that come with it.

The new DRB IVR closely follows the air demand by automatically adjusting the motor speed. Combined with the innovative design of direct driven transmission, this results in average energy savings of 35% and an average cut of 25% in the lifecycle cost of a compressor.

# >>> Optional and standard features

OPTIONS LIST	Factory	Sales				
OIL 8000H	<b>✓</b>	×				
CANOPY HEATER	<b>V</b>	<b>V</b>				
FOOD GRADE OIL	<b>V</b>	×				
OPTION ENERGY RECOVERY	<b>V</b>	<b>V</b>				
HEAVY DUTY INLET FILTER	✓ std on 30 and 37 kW	✓ std on 30 and 37 kW				
COALESCENCE FILTER OPTION 0,1 ppm residual oil content	(with dryer)	(with dryer)				
WATER SEPARATOR DRAIN (WSD) + automatic drain	V	<b>v</b>				
PHASE SEQUENCE RELAY	std	std				
TROPICAL THERMOSTAT	std	std				
WOODEN PACKAGE	<b>V</b>	×				
ES 4000 advanced controller	<b>v</b>	×				
Main isolator SWITCH	V	×				
Silencing baffle	<b>V</b>	<b>V</b>				

<sup>✓ =</sup> available 
X = not available



# **SMART TECHNICAL ADVANTAGES**








#### **CUSTOMIZE YOUR MACHINES** THROUGH A WIDE RANGE OF **OPTIONS:**

- Canopy heaters for low temperature installation



**ES 4000 AS STANDARD ES 4000 ADVANCED AS OPTION** FOR ALL THE MODELS





#### **VERY BIG AIR OIL COOLER AND OPTIMIZED AIR FLOW**

# YOUR ENERGY EFFICIENT AND SOLID PERFORMANCE

>>> DRB 30 - 50 gear driven DRB 30 - 50 IVR direct driven

**DRB 50 IVR D** 



- ooling air filter
- emergency stop
- controller
- oil separator (40 50 hp)
- **5** oil separator (30 35 hp)
- electrical cubicle
- onverter 🕜
- air filter

- air end
- 10 motor
- 👊 fan motor
- 12 gear box (FS)
- 13 direct transmission (IVR)
- 14 water separator drain
- 15 coalescent filter
- 16 dryer



# >>> Energy audit

A frequency driven compressor potentially offers a very energy efficient compressed air installation, with a return on investment of typically 1-2 years. To help you decide to go with a frequency driven compressor or not, Ceccato has created the Energy Cutter, a tool which calculates in an easy way and visually presents the yearly savings that can be obtained from investing in a frequency driven compressor for any specific industry. Besides the Energy Cutter tool, Ceccato offers energy audits, specialized advice to make sure you make the right decision when buying your compressor.





# TECHNICAL DATA



# >>> Fixed speed

FIX SPEED	Max. Working Pressure	Reference Working Pressure	Motor	Power		e Air Delivery ence conditi		Noise Level	Cooling Air flow	Weight	
			H	b		<b>=</b>		<b>—</b>	<b>—</b>	FM	FM D
Model	BAR	PSI	kW	hp	m <sup>3</sup> /h	l/s	cfm	dB(A)	m³/h		kg
	7,5	109			232	65	137				
DRB 30*	8,5	123	22	30	219	61	129	68	2300	445	520
DND 30	10	145			199	55	117				
	13	189			172	48	101				
	7,5	109			271	271 75 160					
DRB 35	8,5	123	26	35	258	72	152	69	4800	460	535
	10	145			236	66	139				
	13	189			205	57	120				
	7,5	109			328	91	193				
DRB 40	8,5	123	30	40	300	83	177	70	4800	560	681
DNB 40	10	145	30		275	76	162	10			
	13	189			240	67	141				
	7,5 109		367	102	216						
DRB 50	8,5	123	37	50	339	94	199	71	4800	623	744
DUD 20	10	145	31	50	304	84	179				
	13	189			275	76	162				

<sup>\*</sup> Available only 400 V 50Hz - IEC - CE

# >>> Variable speed

VARIABLE SPEED		Motor power		Free Air Delivery @ reference conditions											Cooling air flow			
					Min F	AD *	Max.			FAD *								
					7 bar		5 bar		7 bar		10 bar		12,5 bar		<b>)</b>	<del></del>	FM	FM D
Model	BAR / PSI	BAR / PSI	kW	hp	m <sup>3</sup> /h	l/s	m <sup>3</sup> /h	l/s	m <sup>3</sup> /h	l/s	m <sup>3</sup> /h	l/s	m <sup>3</sup> /h	l/s	dB(A)	m <sup>3</sup> /h	<u>•</u>	kg
DRB 30 IVR*	5,5-80	13-188	22	30	46	13	250	69	243	68	211	59	176	49	68	2300	434	503
DRB 35 IVR	5,5-80	13-188	26	35	46	13	290	81	277	77	247	69	205	57	69	4800	444	513
DRB 40 IVR	5,5-80	13-188	30	40	60	17	348	97	327	91	289	80	243	68	70	4800	492	607
DRB 50 IVR	5,5-80	13-188	37	50	64	18	380	106	360	100	325	90	265	74	71	4800	514	629

<sup>\*</sup> Available only 400 V 50Hz - IEC - CE

# >>> Dimensions

	DIMENSIONS									
Model	width mm	height mm	length IVR mm	length IVR + dryer mm						
DRB 30 DRB 35	830	1555	1320	1320						
DRB 40 DRB 50	030	1000	1320	1810						



## **DRB and DRB IVR**





- A high quality product offering you technology you can trust.
- Our products are easy to use and guarantee high reliability.
- Distributors are always nearby ensuring availability of both products and support.
- Choosing our high performance products entails a partnership that will boost your business.
- Safeguarding long-term productivity through optimal serviceability and use of original parts.



# Care. Trust. Efficiency.

#### Care.

Care is what service is all about: professional service by knowledgeable people, using high-quality original parts.

#### Trust.

Trust is earned by delivering on our promises of reliable, uninterrupted performance and long equipment lifetime.

#### Efficiency.

Equipment efficiency is ensured by regular maintenance. Efficiency of the service organization is how Original Parts and Service make the difference.

© 2015, Ceccato. All rights reserved. All mentioned brands, product names, company names, trademarks and service marks are the properties of their respective owners. Our products are constantly being developed and improved. We thus reserve the right to modify product specifications without prior notice. Pictures are not contractually binding

www.ceccato-compressors.com